

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/008878 A1

(51) International Patent Classification⁷: A23L 1/09, A23P 1/08, A21D 13/08, A23L 1/164, 1/00

Jeremy, Z. [GB/GB]; Masterfoods, A Division of Mars UK Ltd., Dundee Road, Slough SL1 4JX (GB).

(21) International Application Number:
PCT/GB2003/003166

(74) Agent: MARLOW, N., S.; Reddie & Grose, 16 Theobalds Road, London WC1X 8PL (GB).

(22) International Filing Date: 23 July 2003 (23.07.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0217077.7 23 July 2002 (23.07.2002) GB

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): MARS, INCORPORATED [US/US]; 6885 Elm Street, McLean, VA 22102-3883 (US).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): JOHNSTON, Andrew, Gordon [GB/GB]; Masterfoods, A Division of Mars Uk Ltd., Dundee Road, Slough SL1 4JX (GB). MEYER,

Published:

— with international search report

[Continued on next page]

(54) Title: BARRIER LAYER BASED ON POLYOL



(57) Abstract: A foodstuff comprising at least two components separated by a barrier layer, the barrier layer being a film of a polyol, polyol derivative or mixture thereof and a method for manufacturing such a foodstuff comprising: applying a polyol, a polyol derivative or mixture thereof to at least part of a surface of a first component to form a film thereon; and bringing at least part of a surface of a second component into contact with the film. The barrier layer is preferably formed by solidification of a molten polyol, polyol derivative or mixture thereof. A barrier layer formed by applying a film of polyol to a non-edible substrate. Use of a film of polyol to inhibit migration into a foodstuff of a liquid with which the foodstuff comes in contact.

WO 2004/008878 A1

WO 2004/008878 A1



— with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- 1 -

BARRIER LAYER BASED ON POLYOL

The present invention relates to novel barrier layers for products such as foodstuffs and to methods of making the novel barrier layers.

The ingress of oxygen and migration of moisture, fat and/or other components in foodstuffs can often severely limit their shelf life. Such processes are difficult to suppress and can lead to oxidation, softening, blooming and invidious changes in taste, texture, smell and appearance of foodstuffs. The application of edible barrier layers, films or coatings to foodstuffs to obviate such problems is known in the art. These layers, films and coatings are intended to prevent, or at least reduce, either the ingress of oxygen or moisture from the atmosphere into a foodstuff or the migration of moisture, fat and/or other components between different layers or phases within a foodstuff. Typically, in foodstuffs where fat migration is likely to be an issue, rather than employing a barrier layer to obviate the problem, fat migration is avoided by manipulation of the ingredients of the foodstuff to omit or reduce the levels of those fats prone to migration.

Many known barrier layers, films or coatings suffer, however, from the disadvantages that they are difficult to apply, expensive or have an adverse effect on the taste or texture of foodstuffs to which they are applied. Furthermore, in order for known layers, films and coatings to be effective as barriers on foodstuffs it is often necessary to apply them in a thick layer, which exaggerates any detrimental effect upon the taste or texture they may have.

- 2 -

According to a first aspect of the present invention there is provided a foodstuff comprising at least two components separated by a barrier layer, the barrier layer being a film of a polyol, polyol derivative or mixture thereof.

5 The two components may be completely or partially separated from one another by the barrier layer.

Preferably, the barrier layer is formed by solidification of a molten polyol, polyol derivative or mixture thereof.

10 Preferably, the barrier layer covers at least 70% of the interface between the two components, more preferably at least 95%.

According to a second aspect of the present invention there is provided a barrier layer formed by applying a film of a polyol, polyol derivative or mixture thereof to a non-edible substrate.

15 Preferably, the barrier layer is formed by the application of a molten polyol, polyol derivative or mixture thereof to at least part of the surface of the non-edible substrate

20 According to a third aspect of the present invention there is provided a non-edible substrate having a barrier layer, the barrier layer being a film of a polyol, polyol derivative or mixture thereof.

Preferably, the barrier layer is formed by solidification of a molten polyol, polyol derivative or mixture thereof.

25 According to a fourth aspect of the present invention there is provided use of a film of a polyol, polyol derivative or mixture thereof to inhibit migration into a foodstuff of a liquid with which the foodstuff comes in contact.

- 3 -

According to a fifth aspect of the present invention there is provided use of a solidified molten polyol barrier layer to inhibit migration into a foodstuff of a liquid with which the foodstuff comes in contact.

- 5 Preferably, the thickness of the barrier layer is about 1.0mm or less, more preferably about 0.5mm or less.

Preferably, the barrier layer is substantially continuous.

- Where the barrier layer is a barrier to moisture migration, preferably the polyol has a solubility at 25°C of less than about 50g/100g H₂O, more preferably less than 30g/100g H₂O.
10 Where the barrier layer is a barrier to moisture migration, preferably the polyol is at least one of mannitol, erythritol or isomalt, most preferably mannitol.

- The barrier layer may comprise a single molten polyol or polyol derivative or a mixture of two or more polyols and/or polyol derivatives.
15

- Preferably, the barrier layer comprises a mixture of at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives, more preferably a mixture of at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.
20

- The barrier layer may also comprise other common additives and ingredients such as colourants, flavourants, acidulants and plasticisers provided that the layer still provides an effective barrier against the migration of moisture, fat and/or other components.
25

- According to a sixth aspect of the present invention there is provided a method of manufacturing a foodstuff comprising at least two components separated by a barrier layer, the barrier layer being a film of a polyol, polyol derivative or
30

- 4 -

mixture thereof comprising: applying a polyol, polyol derivative or mixture thereof to at least part of a surface of a first component to form a film thereon; and bringing at least part of a surface of a second component into contact with the film.

Preferably, the step of forming a film on the first component comprises applying a molten polyol, polyol derivative or mixture thereof to at least part of the surface of the first component and solidifying the molten polyol, polyol derivative or mixture thereof.

Preferably, the polyol, polyol derivative or mixture thereof is applied to the first component by dipping the first component in a molten polyol, polyol derivative or mixture thereof.

Preferably, a mixture of at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives is applied to the first component, more preferably a mixture of at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.

The hard, close packing crystalline or amorphous glass nature of barrier layers according to the invention makes them effective as protection against oxygen ingress and flavour and odour transfer.

Since the barrier layers produced according to the invention are odourless, colourless and clear or translucent, the invention also enables barriers to be applied to foodstuffs and non-edible substrates that do not adversely affect the smell or appearance of the foodstuffs or the non-edible substrates.

The thin barrier layers produced according to the invention are crisp/crunchy. The invention, therefore, also enables

- 5 -

barrier layers to be applied to foodstuffs which advantageously enhance the crisp/crunchy texture of the foodstuffs.

5 A number of polyols, in particular mannitol, erythritol and isomalt, have a low degree of hygroscopicity and low solubility in water. By application of a thin layer of such polyols to substrates, the method of the invention enables barriers to be formed which provide effective and lasting protection against moisture migration. The invention also
10 enables other polyols and/or polyol derivatives, such as maltitol, lactitol, sorbitol, xylitol and isomaltulose, having low solubilities in water at temperatures below 0°C, to be used to form barrier layers effective against moisture migration between components in frozen foodstuffs, for
15 example on biscuits in ice cream.

Applying a thin, for example 0.5mm or less, layer of a molten polyol, polyol derivative or mixture thereof to substrates produces an edible thin, solid, continuous barrier which has improved mechanical strength over for example known fat-based
20 moisture barriers. By reducing the thickness of the layer required to produce an effective barrier, the present invention enables a barrier to be applied to foodstuffs which does not adversely affect the consumer acceptance of the foodstuffs.

25 The polyol barrier layers according to the present invention also exhibit improved temperature stability over known fat-based moisture barriers. Most fats liquify above 40°C and higher melting waxes impart an unpleasant waxy mouth feel to foodstuffs or other substrates to which they are applied. In
30 contrast to most fats, polyols melt at high temperatures, typically above 100°C, and the water solubility of, for example, mannitol increases only slightly with temperature.

- 6 -

The insolubility of polyols in fats and oils makes them suitable for use as barriers against fat migration. Through the formation of solid polyol barrier layers providing effective protection against fat migration, the present invention allows the production of multi-phase or component foodstuffs containing fats which are prone to migration.

The low viscosity of molten polyols enables solid barrier layers according to the invention to be formed by application of polyols to substrates by a wide variety of known techniques, such as dipping, spraying and enamelling. The low viscosity of molten polyols also aids their distribution over the surface of substrates. Consequently, solid barrier layers according to the invention are smooth and uniform.

The invention will be further described, by way of the following examples of specific embodiments thereof:

Example 1

100 cornflakes were dipped into 400g of molten mannitol at 170°C. Each flake was submerged in the molten mannitol before being removed and any excess polyol shaken off. The flakes were then allowed to cool. Cold skimmed milk was then poured onto the dipped cornflakes and also onto eight equally sized portions of untreated cornflakes.

Example 2

300g of mannitol was added to the remaining mannitol from Example 1 and the mixture reheated to 170°C. Whole, shortbread biscuits, halved shortbread biscuits and quartered shortbread biscuits were then dipped halfway into the molten mannitol, before being removed and allowed to cool. Once cool, the other halves of the shortbread biscuits were dipped in the molten mannitol and the biscuits then removed once

- 7 -

again and allowed to cool. The biscuits were then floated in cold skimmed milk for 10 minutes.

Example 3

5 Shortbread biscuits were dipped in molten mannitol as in Example 2 and the biscuits allowed to cool. Once cool, approximately 15 holes were punched in the surface of the biscuits and half of each biscuit then submerged in hot coffee.

10 Example 1 produced cornflakes with a hard, continuous crystalline polyol layer over their entire surface. The polyol layer resulted in no change in the taste or sweetness of the cornflakes, but did result in a slightly crunchier texture compared to the untreated cornflakes. After 3 minutes in cold milk, the crunchiness of the untreated
15 cornflakes began to deteriorate and after 4 minutes in cold milk the untreated cornflakes were no longer crunchy and very soggy. In contrast, after 20 minutes in cold milk the cornflakes with the polyol layer remained as crunchy as the untreated cornflakes were at the time the milk was added.
20 After 25 minutes in cold milk, the crunchiness of the cornflakes with the polyol layer began to deteriorate, resembling that of the untreated cornflakes after 3 minutes in milk.

25 Example 2 produced biscuits with a hard, continuous crystalline polyol layer over their entire surface. The polyol layer resulted in no change in the taste or sweetness of the biscuits, but did result in a slightly crunchier texture. After 10 minutes floating in milk, no moisture penetration of the polyol layer was observed.

30 Example 3 produced biscuits with a hard, continuous crystalline polyol layer over their entire surface as in

- 8 -

Example 2. When the biscuits were dipped in hot coffee a darkening of the biscuits beneath the barrier layer was observed, indicating the absorption of coffee into the biscuits through the holes punched through the barrier layer.
5 The barrier layer, however, remained intact.

Although in the above Examples the substrates were coated using molten mannitol, the same techniques may be employed to coat substrates with molten erythritol, isomalt or other polyols, polyol derivatives or mixture thereof. It will be
10 appreciated that if molten erythritol or isomalt are used instead of molten mannitol a lower temperature may be employed due to the lower melting points of erythritol and isomalt compared to mannitol, about 124°C and 147°C respectively as compared to 167°C.

15 In all of the above Examples the substrates were dipped into the molten polyol in order to form the barrier layer. It will be readily appreciated that a variety of other techniques, such as spraying and enamelling, wherein the polyol is applied to the substrate as a powder and heat then
20 applied to melt the polyol, could alternatively be employed.

While cornflakes and shortbread biscuits are employed as substrates in the Examples given above, it will be readily appreciated by those skilled in the art that barrier layers according to the invention may be applied to a wide variety
25 of other edible and non-edible substrates. It will also be appreciated that while in Examples 1 and 2 the barrier layers are employed to reduce moisture migration, barrier layers according to the invention could be alternatively employed to reduce fat migration, oxygen ingress or odour or flavour
30 transfer. In addition, because of their high mechanical strength and the ease with which they can be applied, it will be appreciated that barrier layers according to the invention may also be employed to prevent melt deformation or, as in Example 3, deformation due to moisture absorption.

- 9 -

It will also be appreciated that while in the above Examples a solid barrier layer was applied to the entire surface area of the substrate, barrier layers according to the invention may be applied to only part of the surface of a substrate.

5 This may be desirable where for example only one surface of a substrate having low water activity is exposed to a high water activity phase. For example, a barrier layer according to the invention may be applied to one surface of a pizza base in order to prevent moisture migration into the base

10 from toppings subsequently applied to that surface.

The application of a solid barrier layer according to the invention to only part of the surface area of a substrate will be further illustrated with reference to the accompanying drawings in which:

15 Figure 1 shows a side elevation of a layered foodstuff comprising a barrier layer according to the invention.

Figure 2 shows a cross-sectional view of a paper plate having a barrier layer according to the invention applied to its upper surface; and

20 Figure 1 shows a layered foodstuff 10 comprising a biscuit layer 11 having a lower surface 12 and an upper surface 13, and a caramel layer 14 on top of the biscuit layer 11, having a lower surface 15, adjacent the upper surface 13 of the biscuit layer 11, and an upper surface 16. A barrier layer

25 17 according to the invention is applied to the upper surface 13 of the biscuit layer 11, which would otherwise be exposed to the lower surface 15 of the caramel layer 14. The barrier layer 17 reduces migration of moisture from the caramel layer 14 into the biscuit layer 11, thereby preventing the biscuit

30 layer 11 from becoming soft and the caramel layer 14 from becoming dry and hard. The crisp, crunchy nature of the barrier layer 17 also enhances the crunchiness of the

- 10 -

biscuit. It will be appreciated that barrier layers according to the invention could also be applied to the lower surface 12 of the biscuit layer 13 and/or upper surface 16 of the caramel layer 14 if desired, for example to prevent moisture ingress from the atmosphere into the biscuit if the lower surface 12 of the biscuit layer is exposed to the air.

Barrier layers according to the invention may be similarly applied for example confectionery products having a coconut creme layer to reduce migration of fat from the coconut into the remainder of the confectionery, for example to prevent discolouration of a chocolate layer which would otherwise be in contact with the coconut.

Figure 2 shows a paper plate 20 having a lower surface 22 and an upper surface 24 which is exposed to foodstuffs during use of the plate. A barrier layer 26 according to the invention is applied to the upper exposed surface 24 of the plate 20 to reduce migration into the plate of moisture, fat and other components from foodstuffs placed on the upper surface 24, thereby preventing mechanical failure of the plate.

Barrier layers according to the invention may be similarly applied for example to the internal surfaces of paper cups to reduce migration into the cups of moisture from beverages contained therein and so prevent mechanical failure of the cups. The edible, colourless, clear or translucent and biodegradable nature of barrier layers according to the invention makes them particularly suitable for this purpose.

Examples of possible substrates to which barrier layers according to the invention could be advantageously applied include:

To reduce moisture migration:
extruded kibbles in moist petfoods;
biscuits dispersed in ice creams;

- 11 -

breakfast cereals;
pizza bases;
biscuit in biscuit and caramel confectionery products;
bread or pastry in prepared sandwiches, wraps and baked
5 goods;
paper plates; and
croutons.

To reduce fat migration:

coconut creme or fat based centres in chocolate confectionery
10 products;
paper plates;
wafers in wafer products with cream fillings; and
chocolate products to reduce soft fat migration driven bloom.

To reduce deformation;

15 chocolate bars/blocks to resist melt deformation in hot
climates;
iced confections to resist melt deformation during non-
chilled transport or storage; and
biscuits to resist deformation when dunked in hot or cold
20 beverages.

- 12 -

CLAIMS

1. A foodstuff comprising at least two components separated by a barrier layer, the barrier layer being a film of a polyol, polyol derivative or mixture thereof.
- 5 2. A foodstuff according to claim 1 in which the barrier layer is formed by solidification of a molten polyol, polyol derivative or mixture thereof.
3. A foodstuff according to claim 1 or 2 wherein the barrier layer has a thickness of 1.0mm or less.
- 10 4. A foodstuff according to claim 1, 2 or 3 wherein the barrier layer has a thickness of 0.5mm or less.
5. A foodstuff according to any preceding claim wherein the barrier layer covers at least 70% of the interface between the two components.
- 15 6. A foodstuff according to any preceding claim wherein the barrier layer covers at least 95% of the interface between the two components.
7. A foodstuff according to any preceding claim wherein the barrier layer is substantially continuous.
- 20 8. A foodstuff according to any preceding claim wherein the barrier layer reduces migration of fat between the two components.
9. A foodstuff according to any preceding claim wherein the barrier layer reduces flavour or odour transfer between the
25 two components.

- 13 -

10. A foodstuff according to any preceding claim wherein the barrier layer reduces migration of moisture between the two components.
11. A foodstuff according to claim 10 wherein the polyol has
5 a solubility at 25°C of less than 50g/100g H₂O.
12. A foodstuff according to claim 10 or 11 wherein the polyol has a solubility at 25°C of less than 30g/100g H₂O.
13. A foodstuff according to claim 10, 11 or 12 wherein the polyol is at least one of mannitol, erythritol or isomalt.
- 10 14. A foodstuff according to any preceding claim wherein the barrier layer comprises at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives.
- 15 15. A foodstuff according to any preceding claim wherein the barrier layer comprises at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.
16. A barrier layer formed by applying a film of a polyol, polyol derivative or mixture thereof to a non-edible substrate.
- 20 17. A barrier layer according to claim 16 formed by the application of a molten polyol, polyol derivative or mixture thereof to at least part of the surface of the non-edible substrate.
18. A barrier layer according to claim 16 or 17 wherein the polyol is at least one of mannitol, erythritol or isomalt.
- 25 19. A barrier layer according to claim 16 or 17 comprising at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives.

- 14 -

20. A barrier layer according to claim 19 comprising at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.
21. A non-edible substrate having a barrier layer, the
5 barrier layer being a film of a polyol, polyol derivative or mixture thereof.
22. A non-edible substrate according to claim 21 in which the barrier layer is formed by solidification of a molten polyol, polyol derivative or mixture thereof.
- 10 23. A non-edible substrate according to claim 21 or 22 wherein the polyol is at least one of mannitol, erythritol or isomalt.
24. A non-edible substrate according to claim 21 or 22 wherein the barrier layer comprises at least 80% by weight
15 mannitol and up to 20% by weight of other polyols or polyol derivatives.
25. A non-edible substrate according to claim 24 wherein the barrier layer comprises at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.
- 20 26. Use of a film of a polyol, polyol derivative or mixture thereof to inhibit migration into a foodstuff of a liquid with which the foodstuff comes in contact.
27. Use of a solidified molten polyol barrier layer to inhibit migration into a foodstuff of a liquid with which the
25 foodstuff comes in contact.
28. Use according to claim 26 or 27 of at least one of mannitol, erythritol or isomalt.

- 15 -

29. Use according to claim 26 or 27 of a mixture of at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives.

5 30. Use according to claim 29 of at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.

31. A method of manufacturing a foodstuff comprising at least two components separated by a barrier layer, the barrier layer being a film of a polyol, polyol derivative or mixture thereof comprising:

10 applying a polyol, polyol derivative or mixture thereof to at least part of a surface of a first component to form a film thereon; and

15 bringing at least part of a surface of a second component into contact with the film.

32. A method according to claim 31 in which the step of forming a film on the first component comprises applying a molten polyol, polyol derivative or mixture thereof to at least part of the surface of the first component and solidifying the molten polyol, polyol derivative or mixture thereof.

33. A method according to claim 31 or 32 wherein the polyol, polyol derivative or mixture thereof is applied to the first component by dipping the first component in a molten polyol, polyol derivative or mixture thereof.

34. A method according to claim 31, 32 or 33 comprising applying a mixture of at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives to the first component.

30 35. A method according to any of claims 31 to 34 comprising applying a mixture of at least 95% by weight mannitol and up

- 16 -

to 5% by weight of other polyols or polyol derivatives to the first component.

36. A foodstuff substantially as described with reference to Figure 1.

5 37. A solid barrier layer substantially as described with reference to the examples.

38. A non-edible substrate substantially as described with reference to Figure 2.

10 39. Use of a polyol, polyol derivative or mixture thereof substantially as described with reference to the examples.

40. A method of manufacturing a foodstuff substantially as described with reference to the examples.

**[Received by the International Bureau on 06 January 2004 (06.01.04):
original claims 1-40 replaced by amended claims 1-31; (4 pages)]**

1. A layered foodstuff comprising at least two component layers separated by a barrier layer, the barrier layer being a film of a solidified melt of at least one polyol.
2. A foodstuff according to claim 1 wherein the barrier layer has a thickness of 1.0mm or less.
3. A foodstuff according to claim 1 or 2 wherein the barrier layer has a thickness of 0.5mm or less.
4. A foodstuff according to any preceding claim wherein the barrier layer covers at least 70% of the interface between the two component layers.
5. A foodstuff according to any preceding claim wherein the barrier layer covers at least 95% of the interface between the two component layers.
6. A foodstuff according to any preceding claim wherein the barrier layer is substantially continuous.
7. A foodstuff according to any preceding claim wherein the barrier layer reduces migration of fat between the two component layers.
8. A foodstuff according to any preceding claim wherein the barrier layer reduces flavour or odour transfer between the two component layers.
9. A foodstuff according to any preceding claim wherein the barrier layer reduces migration of moisture between the two component layers.
10. A foodstuff according to claim 10 wherein the polyol has a solubility at 25°C of less than 50g/100g H₂O.

-18-

11. A foodstuff according to claim 10 or 11 wherein the polyol has a solubility at 25°C of less than 30g/100g H₂O.

12. A foodstuff according to claim 10, 11 or 12 wherein the polyol is at least one of mannitol, erythritol or isomalt.

13. A foodstuff according to any preceding claim wherein the barrier layer comprises at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives.

14. A foodstuff according to any preceding claim wherein the barrier layer comprises at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.

15. Use of a solidified molten polyol barrier layer to inhibit migration into a foodstuff of a liquid with which the foodstuff comes in contact.

16. Use according to claim 15 of at least one of mannitol, erythritol or isomalt.

17. Use according to claim 15 of a mixture of at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives.

18. Use according to claim 17 of at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.

19. A method of manufacturing a layered foodstuff comprising at least two component layers separated by a barrier layer, the barrier layer being a film formed by solidification of at least one molten polyol comprising:
applying at least one molten polyol to at least part of a surface of a first component layer and solidifying the at least one molten polyol to form a film thereon; and

bringing at least part of a surface of a second component layer into contact with the film.

20. A method according to claim 19 wherein the at least one molten polyol is applied to the first component layer by dipping the first layer in the at least one molten polyol.

21. A method according to claim 19 or 20 comprising applying a mixture of at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives to the first component layer.

22. A method according to claim 19, 20 or 21 comprising applying a mixture of at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives to the first component layer.

23. A barrier layer comprising at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives, the barrier layer being a film of a solidified melt of mannitol and, where present, other polyols or polyol derivatives on a non-edible substrate.

24. A barrier layer according to claim 23 comprising at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.

25. A non-edible substrate having a barrier layer comprising at least 80% by weight mannitol and up to 20% by weight of other polyols or polyol derivatives, the barrier layer being a film of a solidified melt of mannitol and, where present, other polyols or polyol derivatives.

26. A non-edible substrate according to claim 25 wherein the barrier layer comprises at least 95% by weight mannitol and up to 5% by weight of other polyols or polyol derivatives.

27. A foodstuff substantially as described with reference to Figure 1.

28. A solid barrier layer substantially as described with reference to the examples.

29. A non-edible substrate substantially as described with reference to Figure 2.

30. Use of a solidified molten polyol barrier layer substantially as described with reference to the examples.

31. A method of manufacturing a layered foodstuff substantially as described with reference to the examples.




Figure 1




Figure 2

INTERNATIONAL SEARCH REPORT

Internat Application No
PCT/ 03/03166

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A23L1/09 A23P1/08 A21D13/08 A23L1/164 A23L1/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 A23L A23P A21D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data, PAJ, FSTA		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 477 858 A (MELNICK DANIEL ET AL) 11 November 1969 (1969-11-11) the whole document	1-20, 26-35
X	US 3 552 979 A (KRUSE NORMAN F) 5 January 1971 (1971-01-05) the whole document	1-20, 26-35
X	US 3 556 814 A (ROSENTHAL HAROLD ET AL) 19 January 1971 (1971-01-19) the whole document	16-18, 21-23
X	US 3 769 438 A (LYNCH M ET AL) 30 October 1973 (1973-10-30) the whole document	1,5-13, 26,28
	-/-	
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art *G* document member of the same patent family		
Date of the actual completion of the international search 28 October 2003		Date of mailing of the international search report 06/11/2003
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Vuillamy, V

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/GB 03/03166

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 375 240 A (PROCTER & GAMBLE) 27 June 1990 (1990-06-27) the whole document -----	1-12,26, 27,31-33
X	EP 0 410 495 A (UNILEVER PLC ; UNILEVER NV (NL)) 30 January 1991 (1991-01-30) the whole document -----	1-12,26, 27,31-33
X	US 5 989 604 A (PELDYAK JOHN ET AL) 23 November 1999 (1999-11-23) figure 6 -----	1,5-12
X	US 5 824 358 A (BYE DOUGLAS A ET AL) 20 October 1998 (1998-10-20) figure 1 -----	1,5-12, 31
X	US 4 260 596 A (MACKLES LEONARD) 7 April 1981 (1981-04-07) the whole document -----	16-25
X	US 4 146 653 A (MADER HELMUT ET AL) 27 March 1979 (1979-03-27) the whole document -----	16-18
A	WO 01 72134 A (NESTLE SA ; LECAT ALEC (GB); MYERS LUCY (GB)) 4 October 2001 (2001-10-04) the whole document -----	1-35
A	FR 2 580 151 A (SAILLY LEON) 17 October 1986 (1986-10-17) the whole document -----	1-35
A	FR 2 312 199 A (MEIJI SEIKA KAISHA) 24 December 1976 (1976-12-24) the whole document -----	1-35

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/GB 03/03166

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3477858	A	11-11-1969	DE 1692600 A1	16-03-1972
US 3552979	A	05-01-1971	NONE	
US 3556814	A	19-01-1971	NONE	
US 3769438	A	30-10-1973	JP 51017177 B	31-05-1976
EP 0375240	A	27-06-1990	US 4960600 A	02-10-1990
			AT 130494 T	15-12-1995
			AU 640357 B2	26-08-1993
			AU 4712689 A	28-06-1990
			CA 2005012 A1	21-06-1990
			CN 1043615 A , B	11-07-1990
			DE 68924904 D1	04-01-1996
			DE 68924904 T2	15-05-1996
			DK 653689 A	22-06-1990
			EP 0375240 A2	27-06-1990
			ES 2080078 T3	01-02-1996
			FI 102656 B1	29-01-1999
			GR 3018204 T3	29-02-1996
			HK 1006134 A1	12-02-1999
			IE 69651 B1	02-10-1996
			JP 2904833 B2	14-06-1999
			JP 3139248 A	13-06-1991
			KR 138520 B1	25-04-1998
			MX 172874 B	18-01-1994
			NZ 231896 A	25-09-1991
			PH 26583 A	19-08-1992
			SG 52336 A1	28-09-1998
EP 0410495	A	30-01-1991	AU 5970790 A	31-01-1991
			CA 2021770 A1	26-01-1991
			EP 0410495 A2	30-01-1991
			JP 3076540 A	02-04-1991
			US 5147670 A	15-09-1992
US 5989604	A	23-11-1999	US 6159508 A	12-12-2000
			US 6228402 B1	08-05-2001
US 5824358	A	20-10-1998	CA 2208387 C	21-08-2001
US 4260596	A	07-04-1981	CA 1141294 A1	15-02-1983
US 4146653	A	27-03-1979	DE 2636152 A1	06-10-1977
			AT 352884 B	10-10-1979
			AT 584277 A	15-03-1979
			AU 510921 B2	17-07-1980
			AU 2768777 A	15-02-1979
			BE 857659 A1	01-12-1977
			CA 1086650 A1	30-09-1980
			CH 630259 A5	15-06-1982
			ES 461516 A1	16-07-1978
			FR 2361105 A1	10-03-1978
			GB 1547527 A	20-06-1979
			HU 176597 B	28-03-1981
			IT 1086479 B	28-05-1985
			JP 1134821 C	14-02-1983

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 03/03166

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4146653	A		JP 53020416 A	24-02-1978
			JP 57025007 B	27-05-1982
			NL 7708808 A	14-02-1978
			SE 431935 B	12-03-1984
			SE 7709050 A	12-02-1978
WO 0172134	A	04-10-2001	AU 4648101 A	08-10-2001
			BR 0109493 A	10-12-2002
			CA 2403165 A1	04-10-2001
			CZ 20023536 A3	18-06-2003
			WO 0172134 A1	04-10-2001
			EP 1267628 A1	02-01-2003
			US 2003072848 A1	17-04-2003
FR 2580151	A	17-10-1986	FR 2580151 A1	17-10-1986
FR 2312199	A	24-12-1976	FR 2312199 A1	24-12-1976